



Sink Installation Guide

Thank you for choosing a quality Sinx by Totara sink.

WE RECOMMEND THAT YOUR SINK IS INSTALLED BY A QUALIFIED PROFESSIONAL TO ENSURE THAT IT IS INSTALLED CORRECTLY. THE WARRANTY MAY NOT BE COVERED IF NOT INSTALLED BY A PROFESSIONAL.

BEFORE INSTALLATION

- Carefully examine the sink making sure that there are no visible defects, scratches, or dents.
- Do not install the sink if any defects are found. Contact your supplier or the customer service team at MM Brands Ltd.

CUT-OUT

- We recommend you have the sink inserted on-site when cutting-out.
- After cutting-out, ensure the raw edge of the cutout is sealed with a suitable sealant to ensure it cannot absorb moisture.

TOP MOUNTING INSTALLATION

- Make sure that you have the sink on site before cutting a hole in the benchtop. Measure the sink before cutting the benchtop to ensure that the hole will be the correct size. Golden rule measure twice cut once!
- Check that the cut-out is at least 10-15mm smaller than the outside edge of the sink and the bowl/bowls will fit inside a cabinet.
- After cutting-out ensure that the raw edge of the benchtop is sealed with a suitable sealant to resist moisture damage.
- When placing sink into the benchtop surface make sure that it is adequately sealed with silicone to resist moisture damage. Refer to the instructions on the Silicone to allow it to cure before using your new sink.
- When you tighten the clips, please do it using a hand tool and not a power tool to ensure you do not over tighten the clips.

UNDERMOUNTING, FLUSHMOUNTING & WELDED INSTALLATION

- We strongly recommend that these are all installed by a suitably qualified and experienced professional installer or Benchtop Fabrication Company.

CLIPPING

- We recommend clips be tightened by hand (not a power tool).
- Do not over-tighten clips.

CARE & MAINTENANCE

- Your new Sinx by Totara sink is quality made and designed to last for many years.
- Basic care will ensure the life of your sink and help it maintain its finish.
- Rinse your sink after each use with a small amount of dishwashing liquid and a soft nylon brush (if needed). Dry with a microfibre cloth.
- Deep clean your sink from time to time with a paste that is recommended for the sink material.
- For more detailed information, see our [Care Guide](#).